

# BOND T-161

## NEOPRENE CONTACT ADESIVE ONE PINT (473 ML)

DISTRIBUTED BY:

MAC'S ANTIQUE AUTO PARTS  
PO BOX 1313  
LOCKPORT, NY 14095-1313

---

# BOND T-161

## NEOPRENE CONTACT ADESIVE ONE PINT (473 ML)

DISTRIBUTED BY  
MAC'S ANTIQUE AUTO PARTS  
PO BOX 1313  
LOCKPORT, NY 14095-1313

### APPLICATION

Formulated for brush or roller application. All surfaces must be clean and free of grease to insure maximum bond strength. Apply adhesive to both surfaces with brush or roller and allow to dry until almost tack-free. Apply pressure to insure intimate contact of the substance.

### STORAGE

For maximum shelf life, store in a cool dry area and keep container tightly sealed. Storage temperatures of 60 degrees to 80 degrees F are recommended. Lower storage temperatures will cause a temporary increase in viscosity. Rotate stock on a "First-in-First out" basis.

### DANGER

Extremely flammable. Toxic. Vapor harmful. Vapors may ignite explosively. Provide fresh air cross ventilation to prevent build-up of vapors. Keep away from heat, sparks and open flame. Do not smoke. Extinguish all flames and pilot lights and turn off all non-explosion proof electrical equipment and sources of ignition during use and until vapors are dissipated. A void prolonged or repeated breathing of the vapors. Close container after use. Contains aliphatic hydrocarbons, toluene and ketones. **KEEP OUT OF REACH OF CHILDREN.** Harmful or fatal if swallowed. If swallowed do not induce vomiting. Call physician immediately.

### IMPORTANT

Suggestions for the use of this product are based on tests believed to be reliable; however, the user should determine suitability for the intended use by his own evaluation. Because the user of the material is beyond our control, neither the seller nor the manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or inability to use this product. Seller and manufacturer's sole obligation shall be replacement of material proved to be defective.

---

### APPLICATION

Formulated for brush or roller application. All surfaces must be clean and free of grease to insure maximum bond strength. Apply adhesive to both surfaces with brush or roller and allow to dry until almost tack-free. Apply pressure to insure intimate contact of the substance.

### STORAGE

For maximum shelf life, store in a cool dry area and keep container tightly sealed. Storage temperatures of 60 degrees to 80 degrees F are recommended. Lower storage temperatures will cause a temporary increase in viscosity. Rotate stock on a "First-in-First out" basis.

### DANGER

Extremely flammable. Toxic. Vapor harmful. Vapors may ignite explosively. Provide fresh air cross ventilation to prevent build-up of vapors. Keep away from heat, sparks and open flame. Do not smoke. Extinguish all flames and pilot lights and turn off all non-explosion proof electrical equipment and sources of ignition during use and until vapors are dissipated. A void prolonged or repeated breathing of the vapors. Close container after use. Contains aliphatic hydrocarbons, toluene and ketones. **KEEP OUT OF REACH OF CHILDREN.** Harmful or fatal if swallowed. If swallowed do not induce vomiting. Call physician immediately.

### IMPORTANT

Suggestions for the use of this product are based on tests believed to be reliable; however, the user should determine suitability for the intended use by his own evaluation. Because the user of the material is beyond our control, neither the seller nor the manufacturer shall be liable for any injury, loss or damage, direct or consequential, arising out of the use or inability to use this product. Seller and manufacturer's sole obligation shall be replacement of material proved to be defective.